




Light distribution (measured with Philips SLM Gen4 3000 lm/4000 K)



H	Beam Diameter (Ø)	Beam Diameter (Ø)
H : 0,5 m	Ø0,2 m	36060 lx
51875 lx		
H : 1,0 m	Ø0,3 m	9015 lx
12969 lx		
H : 1,5 m	Ø0,5 m	4007 lx
5764 lx		
H : 2,0 m	Ø0,7 m	2254 lx
3242 lx		



H	Beam Diameter (Ø)	Beam Diameter (Ø)
H : 0,5 m	Ø0,2 m	33052 lx
44643 lx		
H : 1,0 m	Ø0,4 m	8263 lx
11161 lx		
H : 1,5 m	Ø0,6 m	3672 lx
4960 lx		
H : 2,0 m	Ø0,9 m	2066 lx
2790 lx		



H	Beam Diameter (Ø)	Beam Diameter (Ø)
H : 0,5 m	Ø0,4 m	12287 lx
18253 lx		
H : 1,0 m	Ø0,7 m	3072 lx
4563 lx		
H : 1,5 m	Ø1,1 m	1365 lx
2028 lx		
H : 2,0 m	Ø1,5 m	768 lx
1141 lx		

LED	Made in Germany	50.000h 5 Jahre	CE	220-240V 50/60 Hz	PHILIPS Kooperationspartner
------------	------------------------	----------------------------	-----------	------------------------------	---------------------------------------

LED Data

Philips 1100lm / 830 A+
Philips 1100lm / 840 A+
Philips 1100lm / 930 A+
Philips 2000lm / 830 A+
Philips 2000lm / 840 A+
Philips 2000lm / 930 A+
Philips 3000lm / 830 A+
Philips 3000lm / 840 A+
Philips 3000lm / 930 A+
Philips 4500lm / 830 A+
Philips 4500lm / 840 A+
Philips 4500lm / 930 A+

Different LED manufacturers on request

Description

Suspended Directional Luminaires, gimbal mounted
Mounting frame made of sheet steel
Heat sink made of extruded aluminium black anodised
Housing made of die-cast aluminium with bayonet lock
Safety glass and reflector integrated into the bayonet ring
All visible parts powder coated
Reflector made of aluminium, polished and anodised
Four adjustable wire suspensions
incl. LED driver

Technical Information

Dimension	L x W x H: 296 x 170 x 140mm
Weight	approx. 3.8kg
Colour	Standard: white (RAL 9016), silver (RAL 9006), black (RAL 9005) All colours available Surface fine structure
Reflector design	Inter-changeable bayonet type reflectors
Safety glass	clear or matt
Supply voltage	220-240V, 50/60 Hz
Protection type	IP20
Protection class	I
Light Technology	LED Standard Optional LED for brilliant white and colours in fashion lighting Optional LED for bakery, vegetable and meat products
Supply unit	integrated LED driver
Cooling	passive
LED Lifetime	50.000 operating hours

L = length / **W** = width / **H** = height to heat sink

We reserve the right to change technical details and contents of this data sheet. We are not legally responsible for any unavoidable errors. Product images are examples and may differ from the original.