




Light distribution (measured with Philips SLM Gen4 3000 lm/4000 K)



H	Ø	lx
H : 0,5 m	Ø0,1 m	75818 lx
H : 1,0 m	Ø0,3 m	18954 lx
H : 1,5 m	Ø0,4 m	8424 lx
H : 2,0 m	Ø0,6 m	4739 lx

H	Ø	lx
H : 0,5 m	Ø0,2 m	48758 lx
H : 1,0 m	Ø0,4 m	12190 lx
H : 1,5 m	Ø0,7 m	5418 lx
H : 2,0 m	Ø0,9 m	3047 lx

H	Ø	lx
H : 0,5 m	Ø0,3 m	19674 lx
H : 1,0 m	Ø0,6 m	4919 lx
H : 1,5 m	Ø1,0 m	2186 lx
H : 2,0 m	Ø1,3 m	1230 lx

LED	Made in Germany	50.000h 5 Jahre	CE	220-240V 50/60 Hz	PHILIPS Kooperationspartner
------------	------------------------	----------------------------	-----------	------------------------------	---------------------------------------

LED Data

PPhilips 1100lm / 830 A+
Philips 1100lm / 840 A+
Philips 1100lm / 930 A+
Philips 2000lm / 830 A+
Philips 2000lm / 840 A+
Philips 2000lm / 930 A+
Philips 3000lm / 830 A+
Philips 3000lm / 840 A+
Philips 3000lm / 930 A+
Philips 4500lm / 830 A+
Philips 4500lm / 840 A+
Philips 4000lm / 930 A+

Different LED manufacturers on request

Description

Track Directional Luminaires, tilting and turning
Housing from die-cast aluminium and of sheet steel
Heat sink made of extruded aluminium black anodised
Reflector made of aluminium, polished and anodised
Safety glass and reflector integrated in the cover trim
All visible parts powder coated
Modules for U-CHANNEL or BRIDGE ceiling
incl. LED driver

Technical Information

Electronics	Standard version ON / OFF
Electronics	dimnable DALI
Dimension	B: 151mm / H: 187mm / D: 290mm
Weight	approx. 2,2kg
Colour	Standard: white (RAL 9016), silver (RAL 9006), black (RAL 9005) All RAL colours available Surface fine structure
Reflector design	Inter-changeable bayonet type reflectors
Safety glass	clear
Supply voltage	220-240V, 50/60 Hz
Protection type	IP20
Protection class	I
Lighting Technology	LED Standard Optional LED for brilliant white and colours in fashion lighting Optional LED for bakery, vegetable and meat products
Supply unit	integrated LED driver
Cooling	passive
LED Lifetime	50.000 operating hours

B = breadth / **H** = height / **D** = depth

We reserve the right to change technical details and contents of this data sheet. We are not legally responsible for any unavoidable errors. Product images are examples and may differ from the original.