




Light distribution (measured with Philips SLM Gen4 3000 lm/4000 K)



H	lx	Beam Diameter	lx
0,5 m	75818 lx	Ø0,1 m	55240 lx
1,0 m	18954 lx	Ø0,3 m	13810 lx
1,5 m	8424 lx	Ø0,4 m	6138 lx
2,0 m	4739 lx	Ø0,6 m	3453 lx



H	lx	Beam Diameter	lx
0,5 m	48758 lx	Ø0,2 m	38255 lx
1,0 m	12190 lx	Ø0,4 m	9564 lx
1,5 m	5418 lx	Ø0,7 m	4251 lx
2,0 m	3047 lx	Ø0,9 m	2391 lx



H	lx	Beam Diameter	lx
0,5 m	19674 lx	Ø0,3 m	12950 lx
1,0 m	4919 lx	Ø0,6 m	3238 lx
1,5 m	2186 lx	Ø1,0 m	1439 lx
2,0 m	1230 lx	Ø1,3 m	809 lx

LED	Made in Germany	50.000h 5 Jahre	CE	220-240V 50/60 Hz	PHILIPS Kooperationspartner
------------	------------------------	----------------------------	-----------	------------------------------	---------------------------------------

LED Data

Philips 1100lm / 830 A+
Philips 1100lm / 840 A+
Philips 1100lm / 930 A+
Philips 2000lm / 830 A+
Philips 2000lm / 840 A+
Philips 2000lm / 930 A+
Philips 3000lm / 830 A+
Philips 3000lm / 840 A+
Philips 3000lm / 930 A+
Philips 4500lm / 830 A+
Philips 4500lm / 840 A+
Philips 4500lm / 930 A+

Different LED manufacturers on request

Description

Recessed Directional Luminaires, gimbal mounted
Mounting frame made of sheet steel
Heat sink made of extruded aluminium black anodised
Housing made of die-cast aluminium with bayonet lock
Safety glass and reflector integrated into the bayonet ring
All visible parts powder coated
Reflector made of aluminium, polished and anodised
Easy installation with adjustable mounting brackets
incl. LED driver

Technical Information

Electronics	Standard version ON / OFF
Electronics	dimnable DALI
Dimension	OD: 373,5 x 200mm / CC: 360 x 190mm / RD: 175mm
Ceiling thickness	1 - 20mm
Weight	approx. 2.0kg
Colour	Standard: white (RAL 9016), silver (RAL 9006), black (RAL 9005) All colours available Surface fine structure
Reflector design	Inter-changeable bayonet type reflectors
Safety glass	clear or matt
Supply voltage	220-240V, 50/60 Hz
Protection type	IP20
Protection class	I/II
Light Technology	LED Standard Optional LED for brilliant white and colours in fashion lighting Optional LED for bakery, vegetable and meat products
Supply unit	external LED driver
Cooling	passive
LED Lifetime	50.000 operating hours

OD = outer diameter / **CC** = ceiling cutout / **RD** = recessed depth

We reserve the right to change technical details and contents of this data sheet. We are not legally responsible for any unavoidable errors. Product images are examples and may differ from the original.