







Light distribution (measured with Philips DLM Flex 2000 lm/4000 K)



LED	Made in Germany	50.000h 5 Jahre	CE	220-240V 50/60 Hz	PHILIPS Kooperationspartner
------------	-----------------	--------------------	----	----------------------	---------------------------------------

LED Data

Philips 1100lm / 830 A+
Philips 1100lm / 840 A+
Philips 2000lm / 830 A+
Philips 2000lm / 840 A+
Philips 3000lm / 830 A+
Philips 3000lm / 840 A+

Description

Recessed Luminaires
Recessed Ring from die-cast aluminium with bayonet lock
Heat sink made of extruded aluminium black anodised
Reflector made of aluminium, polished and anodised
All visible parts powder coated
Tool-free installation by spring technology
incl. LED driver

Technical Information

Electronics	Standard version ON / OFF
Electronics	dimnable DALI
Dimension	OD: 194mm / CC: 175mm / RD: 200mm
Ceiling thickness	1 - 20mm
Weight	approx. 1.3kg
Colour	Standard: white (RAL 9016), silver (RAL 9006), black (RAL 9005) All RAL colours available Surface fine structure
Reflector design	specular
Supply voltage	220-240V, 50/60 Hz
Protection type	IP20
Protection class	I/II
Lighting Technology	LED DLM Flex
Supply unit	external LED driver
Cooling	passive
LED Lifetime	50.000 operating hours

OD = outer diameter / **CC** = ceiling cutout / **RD** = recessed depth

We reserve the right to change technical details and contents of this data sheet. We are not legally responsible for any unavoidable errors. Product images are examples and may differ from the original.