



**Light distribution** (measured with Philips SLM Gen4 3000 lm/4000 K)



LED Data

Philips 1100lm / 830 A+  
Philips 1100lm / 840 A+  
Philips 1100lm / 930 A+  
Philips 2000lm / 830 A+  
Philips 2000lm / 840 A+  
Philips 2000lm / 930 A+  
Philips 3000lm / 830 A+  
Philips 3000lm / 840 A+  
Philips 3000lm / 930 A+  
Philips 4500lm / 830 A+  
Philips 4500lm / 840 A+  
Philips 4500lm / 930 A+

Different LED manufacturers on request

Description

Recessed Luminaires  
Mounting frame made of sheet steel  
Heat sink made of extruded aluminium black anodised  
Reflector made of aluminium MIRO  
All visible parts powder coated  
Tool-free installation by spring technology  
incl. LED driver

Technical Information

|                     |  |
|---------------------|--|
| Electronics         | Standard version ON / OFF  |
| Electronics         | Dimmable DALI  |
| Dimension           | OD: 150x150mm / CC: 140x140mm / RD: 160mm  |
| Ceiling thickness   | 1 - 18mm   |
| Weight              | approx. 1,3kg  |
| Colour              | Standard: white (RAL 9016), silver (RAL 9006), black (RAL 9005)<br>All RAL colours available<br>Surface fine structure                   |
| Reflector design    | matt<br>Glare evaluation UGR < 19 (without safety glass)   |
| Supply voltage      | 220-240V, 50/60 Hz   |
| Protection type     | IP 20  |
| Protection class    | I / II   |
| Lighting Technology | LED Standard<br>Optional LED for brilliant white and colours in fashion lighting<br>Optional LED for bakery, vegetable and meat products |
| Supply unit         | external LED driver  |
| Cooling             | passive  |
| LED Lifetime        | 50.000 operating hours   |

**OD** = outer diameter / **CC** = ceiling cutout / **RD** = recessed depth

We reserve the right to change technical details and contents of this data sheet. We are not legally responsible for any unavoidable errors. Product images are examples and may differ from the original.