




Light distribution (measured with Philips SLM Gen4 3000 lm/4000 K)



LED	Made in Germany	50.000h 5 Jahre	CE	220-240V 50/60 Hz	PHILIPS Kooperationspartner
------------	------------------------	----------------------------	-----------	------------------------------	---------------------------------------

LED Data

Philips 2000lm / 830 A+
Philips 2000lm / 840 A+
Philips 2000lm / 930 A+
Philips 3000lm / 830 A+
Philips 3000lm / 840 A+
Philips 3000lm / 930 A+
Philips 4500lm / 830 A+
Philips 4500lm / 840 A+
Philips 4500lm / 930 A+

Different LED manufacturers on request

Description

Surface Mounted Luminaires
Tube housing extruded aluminium
Heat sink made of extruded aluminium black anodised
Bayonet device for connecting to ceiling fixture
Safety glass integrated in the cover trim
All visible parts powder coated
Reflector made of aluminium, polished and anodised
incl. LED driver

Technical Information

Electronics
Electronics

Standard version ON / OFF
dimmable DALI

Dimension
Weight
Colour

OD: 230mm / H: 309mm
approx. 6.6kg
Standard: white (RAL 9016), silver (RAL 9006), black (RAL 9005)
All RAL colours available
Special powder coating for outdoor use possible
Surface fine structure

Reflector design
Safety glass
Supply voltage
Protection type
Protection class
Lighting Technology
Supply unit
Cooling
LED Lifetime

Inter-changeable bayonet type reflectors
clear or matt
220-240V, 50/60 Hz
IP44 or IP65
I
LED Standard
integrated LED driver
passive
50.000 operating hours

OD = outer diameter / **H** = height

We reserve the right to change technical details and contents of this data sheet. We are not legally responsible for any unavoidable errors. Product images are examples and may differ from the original.